

REV	DESCRIPTION	DATE	APPROVED
S0	CREATED DRAWING	2021/10/21	XFY


- TESTING CONDITIONS:
1. VOLTAGE:300V DC/0.1S.
  2. INSULATION RESISTANCE: 10 MOHMS MIN.
  3. CONDUCTIVE RESISTANCE: 5 OHMS MAX.
  4. 100% OPEN AND SHORT ELECTRICAL TEST.

\*ALL MATERIALS ARE RoHS COMPLIANT.

WIRE LIST

P1	PAIR	COLOR	P2	P1	PAIR	COLOR	P2
1	---	RED	1	8	XX	WHITE	19
14	---	DRAIN	14	21	XX	YELLOW1	6
2	XX	WHITE	25	9	XX	WHITE	18
15	XX	WHITE1	12	22	XX	YELLOW2	5
3	XX	WHITE	24	10	XX	WHITE	17
16	XX	WHITE2	11	23	XX	YELLOW3	4
4	XX	WHITE	23	11	XX	WHITE	16
17	XX	WHITE3	10	24	XX	YELLOW4	3
5	XX	WHITE	22	12	XX	WHITE	15
18	XX	WHITE4	9	25	XX	YELLOW--	2
6	XX	WHITE	21	13	---	DRAIN	13
19	XX	WHITE---	8	26	---	BLACK	26
7	XX	WHITE	20	SHELL	---	BRAID	SHELL
20	XX	YELLOW	7				

ITEM	PART NO.	SPECIFICATION	Q'TY	UNIT
⑦	PL00007	HD PE-L M2320	8	g
⑥	PL00011	BLACK PVC 45P	24	g
⑤	SW00059	M2 NICKEL PLATED BRASS SCREW M2*33.2mm	2	PCS
④	SW00059-3	M2.5 NICKEL PLATED BRASS SCREW M2.5*37mm	2	PCS
③	N/A	MDR 26P MALE CONNECTOR	1	SET
②	N/A	SDR 26P MALE CONNECTOR	1	SET
①	N/A	(1P*28#+AL.MYLAR)*11+2C*24#+2DRAIN+Teflon TAPE +AL.MYLAR+BRAID BLACK PVC OD:9.5MM	1	PCS



**SIGNAL**<sup>®</sup>

Shenzhen Signal Electronics co.,Ltd

TITLE  
SDR 26P/M 90° TO MDR  
26P/M PVC CABLE

SGN NO 940026-55-002

DWG NO

CUSTOMER

TOLERANCES ARE:  
DECIMALES .x ±0.5  
ANGLES x.' ±2.0°

THIRD ANGLE PROJECTION

SIZE: A4 UNITS: mm  
SCALE: 1:1 SHEET: 1 OF 1

DRAWN BY	DATE	REV.
CHECKED BY	DATE	S0
CHECKED BY	DATE	
APPROVED BY	DATE	

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.