


REV	DESCRIPTION	DATE	APPROVED
S0	CREATED DRAWING	2024/09/11	ZK



E-CODE

F-CODE

S-CODE

T-CODE

L-CODE

K-CODE

M-CODE


Detailed Product Description:
Waterproof connector rating is IP67
They can not be used permanently under water
Per ISO-20653,IEC60529

Insulation resistance: >100MΩ
Contact resistance of connector ≤10mΩ
Mechanical characteristics: mating / cycle >100cycle
Operating temperature: -25°C ~ +85°C

Contact Pin: Copper alloy with gold-plated
Insulation plastic: PA66

Cable peeling: (covering: 25~30mm, Conductor: 5mm)
Cable OD: 8.0~12.0mm(2 types of waterproof hoses)
Core wire Max: 2.5mm²


ALL MATERIALS ARE RoHS COMPLIANT



TERMINAL:SCREW

Electrical character

Part Number	Contacts	Function	Pin ϕ (mm)	Rated voltage		Rated current	Rated impulse voltage
				A/C	D/C		
121005-01-007S		4+FE	1.5	63V	63V	16A	1.5KV
121305-01-004S		4+PE	1.5	630V	630V	12A	6KV
121406-01-003S		5+PE	1.0	630V	630V	8A	6KV
120504-01-005S		3+PE	1.5	630V	630V	12A	6KV
120503-01-003S		2+PE	1.5	630V	630V	12A	6KV
120604-01-007S		4	1.5	63V	63V	12A	1.5KV
121105-01-003S		4+FE	1.5	63V	63V	16A	1.5KV
121204-01-003S		4	1.5	63V	63V	16A	1.5KV



Shenzhen Signal Electronics Co., LTD

DRAWN BY

DATE

CHECKED BY

DATE

CHECKED BY

DATE

APPROVED BY

DATE

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE
PROPERTY OF SIGNAL COMPANY.
ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN
PERMISSION OF SIGNAL COMPANY IS PROHIBITED.

TITLE M12 FEMALE PLASTIC ASSEMBLY
CONNECTOR(WITH SIGNAL LOGO)

SGN NO

SEE TABLE

REV.

DWG NO

CUSTOMER

S0

TOLERANCES ARE:

DECIMALES

.x ± 0.5 .xx ± 0.20

ANGLES

x' $\pm 2.0'$ x'' $\pm 1.0'$

THIRD ANGLE

PROJECTION

SIZE: A4

UNITS: mm

SCALE:

SHEET: 1 OF