



REV	DESCRIPTION	DATE	APPROVED
S0	CREATED DRAWING	2021/09/01	CYF



Detailed product description:
Protection grade: IP66
Mechanical characteristics: Fit/cycle>4500 cycles
Working temperature: -50°C~+200°C

Connector material
Shell + tail cover: Brass
Locking sleeve: Riveted copper
Insulation clip: Brass
Clamp: Riveted copper
Insulator: PPS
Terminal: Brass
O-ring: silicon rubber

*All materials meet ROHS standard.

Electrical character

Series	PIN Number (Solder)	Terminalø	Test voltage(KV rms)		Rated current(A)
			Pin-Pin	Pin-Shell	
19	1-19	0.7	0.95	1.25	5.0
26	1-26	0.5	0.95	1.30	2.0

SIGNAL® ShenZhen Signal Electronics co., Ltd		TITLE PUSH PULL SELF LOCK CONNECTOR	
		SGN NO SGNFGG.2K	REV. S0
DRAWN BY	DATE	DWG NO	
CHECKED BY	DATE	CUSTOMER	
CHECKED BY	DATE		
APPROVED BY	DATE		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.		TOLERANCES ARE:	THIRD ANGLE PROJECTION
		DECIMALES .x ±0.5 .xx ±0.20	ANGLES .x' ±2.0' .x' ±1.0'
		SIZE: A4	UNITS: mm
		SCALE:	SHEET: 1 OF 1