


REV	DESCRIPTION	DATE	APPROVED
A0	CREATED DRAWING	2025/08/21	XSM



说明:

1.电气特性

额定电压: 交流/直流30V

绝缘电阻: $>100M\Omega$

额定电流: 1A

连接器的接触电阻 $\leq 10m\Omega$

2.机械特性: 插拔/周期 >100 cycle

3.环境特性

操作温度: $-25^{\circ}C \sim +80^{\circ}C$


4.测试条件


导通阻抗: 5Ω MAX

绝缘阻抗: $100M\Omega$ MIN

电 压: DC 300V/0.1S

5.所有材料都符合RoHS标准。



 SIGNAL [®] Shenzhen Signal Electronics co.,Ltd		TITLE M15 19芯公头焊线成型式 (M15*1.0)	
		SGN NO 150019-20-001	REV.
DRAWN BY	DATE	DWG NO SGN01809-0000	A0
CHECKED BY	DATE	CUSTOMER	
CHECKED BY	DATE	TOLERANCES ARE:	
APPROVED BY	DATE	DECIMALES .x ±0.5 .xx ±0.20	THIRD ANGLE PROJECTION 
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.		ANGLES x.° ±2.0' .x' ±1.0'	SCALE: A4
		UNITS: mm	SHEET: 1 OF 1