





REV	DESCRIPTION	DATE	APPROVED
S0	CREATED DRAWING	2024/04/03	ZCH



Material:

- Waterproof rate: IP67
- Housing: Black, ABS 94V-0
- Contact Carrier: PBT, UL Recognized
- Contact Pin: Copper Alloy
- Contact Surface: Gold plated
- Temperature range: -20°C to 60°C
- Connector: D-SUB 25pin Male or Male Shielded (solder pin)
- Seals for cable: OD: $\phi 6.0\text{mm}$ ~ $\phi 10.0\text{mm}$
- One set unassembled in one(1) PE bag



 SIGNAL®		TITLE DB 25/M Plastic Assembly type (OD:6.0-10.0)	
Shenzhen Signal Electronics Co., LTD		SGN NO 910125-01-011	REV.
DRAWN BY	DATE	DWG NO	S0
CHECKED BY	DATE	CUSTOMER	
APPROVED BY	DATE	TOLERANCES ARE: DECIMALES ANGLES .x ±0.5 x.* ±2.0° .xx ±0.20 .x.* ±1.0°	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.		THIRD ANGLE PROJECTION 	SIZE: A4 UNITS: mm
		SCALE:	SHEET: 1 OF 1