




Detailed Product Description:
Waterproof connector rating is IP67
They can not be used permanently under water
Per ISO-20653,IEC60529


Cable OD: 5~7.2mm
Core wire: 1.0mm² max 26~18AWG

Other Specification
Contact PIN: Phosphor bronze with Gold plating.
Coupling nut/screw: Brass with nickel plating
Insulation plastic: PA66+GF
Operating temperature: -25°C ~ +85°C

*ALL MATERIALS ARE RoHS COMPLIANT.



Terminal: screw



Electrical character

Part Number	Contacts	Rated voltage		Rated current	Contact Resistance
		A/C	D/C		
080103-02-00X		60V	60V	3A	10mΩ
080104-02-010	✓	30V	30V	3A	10mΩ



Shenzhen Signal Electronics Co., LTD

DRAWN BY	DATE
CHECKED BY	DATE
APPROVED BY	DATE

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY.
ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.

TITLE M8 A CODE FEMALE METAL ASSEMBLY CONNECTOR

SGN NO 080104-02-010 REV.

DWG NO

CUSTOMER

TOLERANCES ARE:

DECIMALES ANGLES

.x ±0.5 x.* ±2.0°

.xx ±0.20 .x.* ±1.0°

THIRD ANGLE PROJECTION

SIZE: A4 UNITS: mm

SCALE: SHEET: 1 OF 1