



REV	DESCRIPTION	DATE	APPROVED
S0	CREATED DRAWING	2020/04/22	ZK

Detailed Product Description:
 Waterproof connector rating is IP67
 They can not be used permanently under water
 Per ISO-20653,IEC60529


Mechanical characteristics: mating / cycle >100cycles
 Operating temperature: -25°C ~ +85°C



ALL MATERIALS ARE RoHS COMPLIANT



Electrical character

Part Number	Contacts	Rated voltage		Rated current	Contact Resistance	Cable OD (mm)
		A/C	D/C			
080103-02-001S		50V	60V	3A	10mΩ	3~4.5
080104-02-001S		50V	60V	3A	10mΩ	3~4.5



 SIGNAL®		TITLE M8 A CODE FEMALE PLASTIC ASSEMBLY CONNECTOR	
Shenzhen Signal Electronics Co., LTD		SGN NO 080103~04-02-001S	REV.
DRAWN BY	DATE	DWG NO	S0
CHECKED BY	DATE	CUSTOMER	
APPROVED BY	DATE	TOLERANCES ARE: DECIMALES ANGLES	THIRD ANGLE PROJECTION 
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.		.x ±0.5	x.* ±2.0°
		.xx ±0.20	.x.* ±1.0°
		SIZE: A4	UNITS: mm
		SCALE:	SHEET: 1 OF 1