

Protection degree:IP67 in locked status
Per ISO-20653,IEC60529

Connector Electrical character

Rating voltage: IEC

Insulation resistance: >100MΩ

Rating current: IEC

Contact resistance of connector ≤10mΩ

Mechanical characteristics: mating/cycle >100 cycle

Other Specification



Contact PIN: Brass copper with Gold plating.

Coupling nut/screw/shell: Brass nickel plated

Insulation plastic: PA66+GF

Operating temperature: -25°C ~ +85°C

*ALL MATERIALS ARE RoHS COMPLIANT.



Electrical character

Part Number	Contacts	Rated voltage		Rated current	Contact Resistance	Cable OD(mm)
		AC	DC			
090002-02-001		125V	125V	4A	3mΩ	3~5.5mm
090003-02-001		125V	125V	4A	3mΩ	3~5.5mm
090004-02-001		125V	125V	3A	3mΩ	3~5.5mm
090005-02-001		125V	125V	3A	3mΩ	3~5.5mm
090007-02-001		125V	125V	1A	3mΩ	3~5.5mm
090008-02-001		125V	125V	1A	3mΩ	3~5.5mm



Shen Zhen Signal Electronics co.,Ltd

DRAWN BY	DATE
CHECKED BY	DATE
APPROVED BY	DATE

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY.
ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.

TITLE
M9 FEMALE ASSEMBLY CONNECTOR

SGN NO SEE LIST REV.

DWG NO

CUSTOMER

TOLERANCES ARE:

DECIMALES ANGLES

.x ±0.5 x.° ±2.0' .xx ±0.20 .x.° ±1.0'

THIRD ANGLE PROJECTION

SIZE: A4 UNITS: mm

SCALE: SHEET: 1 OF 1