



REV	DESCRIPTION	DATE	APPROVED
S0	CREATED DRAWING	2021/12/07	CYF

Detailed Product Description:
 Waterproof connector rating is IP67
 They can not be used permanently under water
 Per ISO-20653,IEC60529

Mechanical characteristics: mating / cycle >100cycles
 Operating temperature: -25°C ~ +85°C

ALL MATERIALS ARE RoHS COMPLIANT



Electrical character

Part Number	Contacts	Rated voltage		Rated current	Contact Resistance	Cable OD (mm)
		A/C	D/C			
080103-02-002		50V	60V	3A	10mΩ	3~5.5
080104-02-002		50V	60V	3A	10mΩ	3~5.5
080205-02-001		30V	30V	3A	10mΩ	3~5.5
080106-02-001		30V	30V	1.5A	10mΩ	3~5.5
080108-02-001		30V	30V	1.5A	10mΩ	3~5.5

SIGNAL
 Shen Zhen Signal Electronics co.,Ltd

TITLE: M8 FEMALE CONNECTOR WITH SHIELD

SGN NO: SEE TABLE
 DWG NO: SEE TABLE
 CUSTOMER: SEE TABLE
 REV: S0

DRAWN BY: _____ DATE: _____
 CHECKED BY: _____ DATE: _____
 APPROVED BY: _____ DATE: _____

TOLERANCES ARE:
 DECIMALES: .x ±0.5, .xx ±0.20
 ANGLES: x.* ±2.0°, .x.* ±1.0°

THIRD ANGLE PROJECTION:

SIZE: A4 UNITS: mm
 SCALE: SHEET: 1 OF 1

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.