





REV	DESCRIPTION	DATE	APPROVED
S0	CREATED DRAWING	2024/12/05	ZHY



Electrical character

Rated voltage	50V/AC,63V/DC	
Rated current	2A	8A
Mechanical characteristics (mating cycle)	>100	
Degree of protection (ISO-20653,IEC60529)	IP67	
Operating temperature (depending on cable quality)	-25°C ~ +80°C	
Destructive withstand force between connector and overmold exceeds	**kgf	
Tightening torque (range)	0.4~1.8Nm	
Pollution degree	3	
ALL MATERIALS ARE RoHS COMPLIANT		

 SIGNAL [®] Shenzhen Signal Electronics co.,Ltd		TITLE SPE-I M12 HYBRID 7PIN FEMALE CONNECTOR CABLE	
		SGN NO 121507-06-001	REV. S0
DRAWN BY	DATE	DWG NO	CUSTOMER
CHECKED BY	DATE	APPROVED BY	
CHECKED BY	DATE	DATE	
TOLERANCES ARE:		THIRD ANGLE PROJECTION	
DECIMALES	ANGLES		
.x ±0.50	x.* ±2.0'	SIZE: A4	UNITS: mm
.xx ±0.20	.x' ±1.0'	SCALE: 1:1	SHEET: 1 OF 1
<small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.</small>			