




RECOMMENDED PANEL
CUTOUT SIZE



Electrical character

Rated voltage	50V/AC,63V/DC	
Rated current	2A	8A
Mechanical characteristics (mating cycle)	>100	
Degree of protection (ISO—20653,IEC60529)	IP67	
Operating temperature (depending on cable quality)	-25°C ~ +80°C	
Destructive withstand force between connector and overmold exceeds	**kgf	
Tightening torque (range)	0.4~1.8Nm	
Pollution degree	3	
ALL MATERIALS ARE RoHS COMPLIANT		



Shenzhen Signal Electronics co.,Ltd

DRAWN BY	DATE
CHECKED BY	DATE
CHECKED BY	DATE
APPROVED BY	DATE

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE
PROPERTY OF SIGNAL COMPANY.
ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN
PERMISSION OF SIGNAL COMPANY IS PROHIBITED.

TITLE
SPE-I M12 HYBRID 7PIN REAR
LOCKING PANEL FEMALE CONNECTOR

SGN NO	121507-04-002	REV.
DWG NO		
CUSTOMER		SO

TOLERANCES ARE: DECIMALES ANGLES	THIRD ANGLE PROJECTION	SIZE: A4	UNITS: mm
.x ±0.50 .xx ±0.20	x.* ±2.0° .x.* ±1.0°	SCALE:1:1	SHEET:1 OF 1