


REV	DESCRIPTION	DATE	APPROVED
S0	CREATED DRAWING	2023/03/13	ZCH



Detailed product description:

Connector electrical character

Rating voltage: 100V AC,140V DC,

Rating current : 2A

Insulation resistance: >1000M ohms

Contact resistance of connector ≤10m ohms

Dielectric withstanding voltage: 300V AC R.M.S.Max.

Mechanical characteristics:

Mating cycles >500 cycles


Operating temperature: -25°C ~ +85°C

Storage temperature: -10°C ~ +60°C

Cable OD: Ø5.0mm

Applicable Wire: 0.15mm²(26AWG),

*All materials are RoHS compliant.



 SIGNAL® Shenzhen Signal Electronics co.,Ltd		TITLE PUSH PULL 6PIN PLUG (SOLDER TYPE FORM CONTACT)	
DRAWN BY	DATE	SGN NO 950106-21-004	REV.
CHECKED BY	DATE	DWG NO SGN01004-1566	SO
CHECKED BY	DATE	CUSTOMER	
APPROVED BY	DATE	TOLERANCES ARE: DECIMALES ANGLES .x ±0.5 .xx ±0.20 x.' ±2.0' x' ±1.0'	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.		THIRD ANGLE PROJECTION	
		SIZE: A4	UNITS: mm
		SCALE: 1:1	SHEET: 1 OF 1